

Snell & Wilmer

L.L.P.

LAW OFFICES

One Arizona Center
 Phoenix, Arizona 85004-2202
 602.382.6000 P
 602.382.6070 F
 swlw.com

DENVER

IRVINE

LAS VEGAS

PHOENIX

SALT LAKE CITY

TUCSON

RECEIVED
CENTRAL FAX CENTER

MAY 30 2006

FACSIMILE TRANSMISSION

DATE: May 30, 2006

TIME IN:
TIME OUT:

TO:

Name	Fax Number	Phone Number
Attn: Certificate of Correction Branch U.S. Patent and Trademark Office	571-273-8300	

FROM: John Platt

PHONE: 602-382-6367

RE: U.S. Patent No. 7,035,617

MESSAGE:

Request for Certificate of Correction (3 Pages)

Thank you.
 John H. Platt

Please confirm receipt of this facsimile.

ORIGINAL DOCUMENT: Will not be sent

NUMBER OF PAGES (Including Cover): 7

CONFIRMATION NO.:

CLIENT MATTER NO.: 36956.1000

PLEASE RETURN TO: Kim L. Brown
16S21

PERSONAL FAX: No

REQUESTOR: John Platt

DIRECT LINE: 602-382-6367

IF YOU HAVE NOT PROPERLY RECEIVED THIS TELECOPY, PLEASE CALL US AT (602) 382-6075.
 OUR FACSIMILE NUMBER IS (602) 382-6070.

THE INFORMATION CONTAINED IN THIS FACSIMILE MESSAGE IS ATTORNEY PRIVILEGED AND CONFIDENTIAL INFORMATION INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT, OR THE EMPLOYEE OR AGENT RESPONSIBLE TO DELIVER IT TO THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION OR COPYING OF THIS COMMUNICATION IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, PLEASE IMMEDIATELY NOTIFY US BY TELEPHONE, AND RETURN THE ORIGINAL MESSAGE TO US AT THE ABOVE ADDRESS VIA THE U.S. POSTAL SERVICE. THANK YOU

1341020

BEST AVAILABLE COPY

MAY 30 2006 16:09 FR SNELL WILMER PHX 3 602 382 6070 TO 915712738300

P.02

**RECEIVED
CENTRAL FAX CENTER****MAY 30 2006****CERTIFICATE OF FACSIMILE PURSUANT TO 37 C.F.R. § 1.8**

I hereby certify that this correspondence is being transmitted via facsimile to the United States Patent and Trademark Office at (571) 273-8300 and is addressed to: Attn: Certificate of Correction Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on:

Date: 5/30/06 By: Kim L. Brown

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**PATENT**

Applicant:	Kenneth V. Buer et al.	Docket No.:	36956.1000
Patent No.:	7,035,617	Serial No.:	10/066,024
Issue Date.:	April 25, 2006	Filing Date:	January 29, 2002
Title:	HIGH POWER BLOCK UPCONVERTER	Confirmation No.:	2094

REQUEST FOR CERTIFICATE OF CORRECTION
UNDER 37 C.F.R. §§ 1.322

Attn: Certificate of Correction Branch
Commissioner for Patents
PO Box 1450
Alexandria, VA 22313-1450

Dear Commissioner:

Pursuant to 37 C.F.R. §§1.322, Patentee hereby requests a Certificate of Correction be issued to correct errors noticed in the claims. In accordance with the provisions of 37 C.F.R. §§1.322 of the Rules of Practice, approval of the attached Certificate of Correction for the above-identified patent is requested.

The errors in Claims 1, 7, 11, and 12 were made by the Office. (Compare to listing of claims in the last Response to Office Action dated October 27, 2005.) Claims 1, 7, 11, and 12, should read:

1. A block-up converter comprising:
a subharmonic mixer;

wherein said subharmonic mixer is configured to receive a first input signal,

wherein said first input signal is an intermediate frequency signal;

wherein said subharmonic mixer is further configured to receive a second input

U.S. Patent No. 7,035,617
Docket No. 36956.1000

- signal, wherein said second input signal is a local oscillator signal in the Ku band or lower;
- wherein said subharmonic mixer is configured to output a RF signal having a frequency greater than 26 GHz;
- a filter configured to receive said RF signal and filter unwanted spurious signals which may be present in said RF signal; and
- a power amplification device configured to receive said RF signal and to provide a desired signal gain;
- wherein said subharmonic mixer, said filter, and said amplification device are located on a single multi-chip module, such that all signal interfaces with said multi-chip module occur at frequencies less than 26 GHz except for the final output of said RF signal from said multi-chip module;
- wherein said multi-chip module is configured to be surface mounted using a lead frame interface;
- wherein said block-up converter is configured to be a high power block-up converter, wherein high power is defined to be any power greater than 1 ~~Watt~~ Watt; and
- wherein said block-up converter is configured to provide a high frequency output, wherein high frequency is defined to be any frequency greater than 26 GHz.
7. The ~~block-up~~ block-up converter of claim 6, wherein said multi-chip module is configured to be surface mounted using a lead frame interface.
11. The block-up converter of claim 6, wherein said ~~multi-chip~~ multi-chip module is configured to be a drop-in component within the next higher assembly level.
12. A method for assembling a block-up converter on a single multi-chip module, the method comprising the steps of:
- electrically connecting a subharmonic mixer on a multi-chip module to a filter on said multi-chip module;
- wherein said subharmonic mixer is configured to receive a first input signal,
- wherein said first input signal is an intermediate frequency signal;
- wherein said subharmonic mixer is further configured to receive a second input

U.S. Patent No. 7,035,617
Docket No. 36956.1000

signal, wherein said second input signal is a local oscillator signal in the Ku band or lower;
wherein said subharmonic mixer is configured to output a RF signal having a frequency greater than 26 GHz;
wherein said filter is configured to receive said RF signal and filter unwanted spurious signals which may be present in said RF signal; and
electrically connecting said filter to a power amplification device that is also located on said multi-chip module,
wherein said power amplification device is configured to receive said ~~RERF~~ signal and to provide a desired signal gain;
wherein said block-up converter is configured to be a high power block-up converter, wherein high power is defined to be any power greater than 1 Watt; and
wherein said block-up converter is configured to provide a high frequency output, wherein high frequency is defined to be any frequency greater than 26 GHz.

The Commissioner is hereby authorized to charge any fees which may be required for the Certificate of Correction to Deposit Account No. 19-2814. **A duplicate copy of this document is enclosed.**

If there are any questions or unresolved issues, the undersigned would welcome a telephone call to the number shown below.

Dated: May 30, 2006

Respectfully submitted,

By John H. Platt
John H. Platt
Reg. No. 47,863

SNELL & WILMER L.L.P.
One Arizona Center
400 East Van Buren
Phoenix, AZ 85004-2202
Telephone: (602) 382-6367
Facsimile: (602) 382-6070
Email: jplatt@swlaw.com

RECEIVED
CENTRAL FAX CENTER

MAY 30 2006

CERTIFICATE OF FACSIMILE PURSUANT TO 37 C.F.R. § 1.8

I hereby certify that this correspondence is being transmitted via facsimile to the United States Patent and Trademark Office at (571) 273-8300 and is addressed to: Attn: Certificate of Correction Branch, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on:

Date: 5/30/06 By: Kim L. Brown

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PATENT

Applicant:	Kenneth V. Buer et al.	Docket No.:	36956.1000
Patent No.:	7,035,617	Serial No.:	10/066,024
Issue Date::	April 25, 2006	Filing Date:	January 29, 2002
Title:	HIGH POWER BLOCK UPCONVERTER	Confirmation No.:	2094

REQUEST FOR CERTIFICATE OF CORRECTION
UNDER 37 C.F.R. §§ 1.322

Attn: Certificate of Correction Branch
Commissioner for Patents
PO Box 1450
Alexandria, VA 22313-1450

Dear Commissioner:

Pursuant to 37 C.F.R. §§1.322, Patentee hereby requests a Certificate of Correction be issued to correct errors noticed in the claims. In accordance with the provisions of 37 C.F.R. §§1.322 of the Rules of Practice, approval of the attached Certificate of Correction for the above-identified patent is requested.

The errors in Claims 1, 7, 11, and 12 were made by the Office. (Compare to listing of claims in the last Response to Office Action dated October 27, 2005.) Claims 1, 7, 11, and 12, should read:

1. A block-up converter comprising:
a subharmonic mixer;
wherein said subharmonic mixer is configured to receive a first input signal,
wherein said first input signal is an intermediate frequency signal;
wherein said subharmonic mixer is further configured to receive a second input

U.S. Patent No. 7,035,617
Docket No. 36956.1000

- signal, wherein said second input signal is a local oscillator signal in the Ku band or lower;
- wherein said subharmonic mixer is configured to output a RF signal having a frequency greater than 26 GHz;
- a filter configured to receive said RF signal and filter unwanted spurious signals which may be present in said RF signal; and
- a power amplification device configured to receive said RF signal and to provide a desired signal gain;
- wherein said subharmonic mixer, said filter, and said amplification device are located on a single multi-chip module, such that all signal interfaces with said multi-chip module occur at frequencies less than 26 GHz except for the final output of said RF signal from said multi-chip module;
- wherein said multi-chip module is configured to be surface mounted using a lead frame interface;
- wherein said block-up converter is configured to be a high power block-up converter, wherein high power is defined to be any power greater than 1 ~~Watt~~ Watt; and
- wherein said block-up converter is configured to provide a high frequency output, wherein high frequency is defined to be any frequency greater than 26 GHz.
7. The ~~block-up~~ block-up converter of claim 6, wherein said multi-chip module is configured to be surface mounted using a lead frame interface.
11. The block-up converter of claim 6, wherein said ~~multi-chip~~ multi-chip module is configured to be a drop-in component within the next higher assembly level.
12. A method for assembling a block-up converter on a single multi-chip module, the method comprising the steps of:
- electrically connecting a subharmonic mixer on a multi-chip module to a filter on said multi-chip module;
- wherein said subharmonic mixer is configured to receive a first input signal,
- wherein said first input signal is an intermediate frequency signal;
- wherein said subharmonic mixer is further configured to receive a second input

U.S. Patent No. 7,035,617
Docket No. 36956.1000

signal, wherein said second input signal is a local oscillator signal in the Ku band or lower;
wherein said subharmonic mixer is configured to output a RF signal having a frequency greater than 26 GHz;
wherein said filter is configured to receive said RF signal and filter unwanted spurious signals which may be present in said RF signal; and
electrically connecting said filter to a power amplification device that is also located on said multi-chip module,
wherein said power amplification device is configured to receive said ~~PERF~~ signal and to provide a desired signal gain;
wherein said block-up converter is configured to be a high power block-up converter, wherein high power is defined to be any power greater than 1 Watt; and
wherein said block-up converter is configured to provide a high frequency output, wherein high frequency is defined to be any frequency greater than 26 GHz.

The Commissioner is hereby authorized to charge any fees which may be required for the Certificate of Correction to Deposit Account No. 19-2814. A duplicate copy of this document is enclosed.

If there are any questions or unresolved issues, the undersigned would welcome a telephone call to the number shown below.

Dated: May 30, 2006

Respectfully submitted,

By John H. Platt
John H. Platt
Reg. No. 47,863

SNELL & WILMER L.L.P.
One Arizona Center
400 East Van Buren
Phoenix, AZ 85004-2202
Telephone: (602) 382-6367
Facsimile: (602) 382-6070
Email: jplatt@swlaw.com

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.